

Clamco 6800CS Side Sealer

Automatically seal packages of virtually any length

The Clamco 6800CS automatic side sealer is a highly efficient side sealer that combines a hot knife end seal with an adjustable seal and trim knife. The trim knife is actuated when the product moves past the cross seal. Compared to conventional automatic L-bar sealers, the 6800CS can pack products of any length at high speed.

The 6800CS can deliver conveyor speeds up to 100 ft/min (140 ft/min for the 6800CS-XL) and wrap up to 4,200 packs per hour. The system is perfect for polyolefin or polyethylene center folded shrink film. Packages can be as large as 8" high, 16" wide on the 6800CS. For the 6800CS-XL version packages can be as large as 11" high, 23" wide. Virtually any length is possible on both units.

Film feed is achieved by a film inverter, permitting product to be delivered to the sealer by conveyor. This gives the 6800CS a wide range of product height to width size choices. The 6800CS has beginning and end product sensors to maintain a consistent bag length around the product. The sensors provide optimum film shrink around the product while traveling through the optional shrink tunnel.

The 6800CS can be set up in minutes, is easy to program, and offers multiple operating modes for performance and convenience. Paired with a Clamco heavy duty shrink tunnel, the 6800CS makes an outstanding high production shrink wrapping system. This CE compliant machine is one of the most versatile automatic side sealers on the market today and includes a 2 year limited warranty.

Operating features


- Easy to navigate interface for operators of most skill levels
- Display of key packing statistics, including production rate and efficiency
- Continual monitoring of product length to detect packing errors
- Film-economizer wheels reduce scrap and improve final package appearance
- Trim take-up wheel keeps the work area clean
- Automatic product length detection allows for feeding of random length packages



Closing conveyor for small length product 6" or less, & multi-packs (6800CS only)



Safety photocell (optional) prevents cross seal bar from contacting the package



Film roll guides allow for a wide range of films with easy adjustment of the perf wheels

Sealing features

- Closing conveyor for smooth product transfer (6800CS only)
- Rounded cross seal bar decreases film breakage
- PTFE-coated side seal works with most shrink films
- Automatic adjustment of cross seal bar opening based on product height increases wrapping speed

Set-up features

- Low film cradle with film inverter for easy film loading and threading
- Quick changeover and 20 program memory allows for product setup in less than five minutes
- Automatic seal centering on both the side seal and the cross seal, for a clean looking package

PAC Machinery

More experience. Better choices.

Safety features

- Fully enclosed guarding ensures operator safety
- Smooth and quiet operation reduces plant noise
- Compliance with CE regulations ensures improved safety and design
- Easy to reach emergency stop button

Specifications

Model	6800CS	6800CS-XL
Production capacity	up to 70 cycles/min	up to 70 cycles/min
Conveyor speed	up to 100 ft/min	up to 140 ft/min
Cross seal bar width	19.75"	27.5"
Product width (max)	16"	23"
Product height (max)	8"	11"
Product length (max)	unlimited	unlimited
Film width (max)	13"–23.5"	up to 33.5"
Film roll diameter (max)	13.75"	13.75"
Electrical	220V, 15A, 1ph	220V, 15A, 1ph
Air	Not required	Not required
Size	75" L x 58" W x 60" H	105" L x 75" W x 65" H
Shipping weight	1,800 lbs	2,100 lbs
Warranty	2 years	2 years



The robust design of the 6800CS side sealer provides consistently strong and attractive seals for greater retail package appeal and higher levels of throughput.

Options and Accessories

- Polyethylene cross seal bar to use 0.6–3 mil polyethylene film
- Stainless steel frame for applications in the food industry
- Safety photocell to ensure cross seal bar does not make contact with product
- 3' Infeed conveyor
- 6' Infeed conveyor
- Irregular Product Sensor to detect products with an inconsistent shape
- Opaque Film Sensor for coex mailer film



Paired with a Clamco heavy duty shrink tunnel, the 6800CS makes an outstanding high production shrink wrapping system.

Contact us today:

1 (800) 985-9570 ■ sales@pacmachinery.com

PAC Machinery

More experience. Better choices.

775 Berea Industrial Parkway, Berea OH 44017 ■ pacmachinery.com

Specifications subject to change without notice

ReviveWrap

Better Film. Better Choice. Better Planet.



Made with
up to
30%
recycled
content

Recyclable at
store drop-off

for shrink equipment

You can order your ReviveWrap shrink film from PAC Machinery for your shrink equipment

pacmachinery.com