



NOTE: 256T HAS 6 MTG. HOLES, USING BOTH 254T AND 256T "2F" LOCATIONS.

FRAME	"C"	"B"	"BV"
254T	23.80	10.25	9.16
256T	25.50	12.00	10.01

			TOLERANCES UNLESS SPECIFIED		LEESON	ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN DRZ 05/23/01			
			DEC.	METRIC				CHK		
02	3.75 DIM WAS 4.00, & 4.75 DIM WAS 4.25, REV'D TO	BJB 09/23/03	.X	±.25	TITLE	OUTLINE - 250T FRAME RIGID, "C"-FACE, NEW CON-BOX	SCALE 5=16			
01	MATCH NEMA RIGID "C"-FACE" 250T FRAME SPECS		.XX	±.76	MAT'L	CAST IRON	REF			
01	REDRAWN TO CURRENT CAD STANDARDS	CJK 08/06/01	.XXX	±.127	FINISH		FMF			
NO.	REVISION	BY & DATE	CHK	ANG ±1/2'			PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE 16956360	SIZE B	DRAWING NO. 169563-60	REV. 02
						DIST				