



- NOTES: 1) Dimensions in inches (Millimeters)  
 2) Compressed Air, Minimum 3/4 (20) I.D. Supply Line  
 1 SCF (29L) Per Cycle At 90 PSI (6 bar)  
 3) Electrical Requirement:  
 1 Kilowatt, 3 Phase, Standard 230 Volts  
 4) Dimensions marked are for optional  
 outfeed guarding

Dimensions And Specifications Subject To  
 Change And Dependent on Specific Case  
 Characteristics And Options Ordered

FORMER LAYOUT, TAPE, 25" DISCHARGE

Drawn By	Date	Checked By	Date	Model
A.C.	22JAN97			WFT-S
Assy.		Rev.		Drawing No.
				70-516

**wexar** Packaging Machinery Ltd.

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO WEXAR PACKAGING MACHINERY LTD. AND MUST NOT BE REPRODUCED, DESCRIBED TO OTHERS, OR USED FOR ANY OTHER PURPOSE OTHER THAN THE PURPOSE FOR WHICH IT IS FURNISHED WITHOUT PRIOR WRITTEN CONSENT OF WEXAR PACKAGING MACHINERY LTD.

TELEPHONE U.S. 630 983-6666 CANADA 604 930 9300  
 FAX 630 983-6948 604 930 9368