

ST-822CM
STB-822CL

Radiant Convection Tunnels



MADE IN U.S.A

Distributed by:

Features, Functions & Benefits

- Robust AC inverter duty motors
- Easy to read L.E.D. display(heat control)
- Infinitely adjustable fan speed
- Energy efficient heater design
- Lighted viewing window
- Easily accessible internal components (heaters)
- Heavy duty construction
- Durable powder coat finish
- Various belt options available
- Automatic cool down
- Adjustable height legs
- 150 feet per minute belt speed
- Independently controlled zones, heat & airflow.

Specifications:

	ST-822CM	STB-822CL
Chamber Opening:	8"H x 22"W	8"H x 22"W
Chamber Length:	60"L	120"L
Electrical:	230V, 46 amp, 3 phase	230V, 60 amp, 3 phase
Conveyor Height:	Adj. from 30" to 36"	Adj. from 30" to 36"
Conveyor Speed:	0 - 150 FPM	0 - 200 FPM
Conveyor Width:	15"	20"
Footprint:	92"L x 36"W x 66"H	144"L x 43"W x 66"H
Shipping Weight:	800 lbs.	1,400 lbs.

ST-822CM STB-822CL

A=	60.00"	120.25"
B=	22.00"	24.25"
C=	92"	144"
D=	Allow 72"	Allow 72"
E=	30-36"	30-36"
F=	38"	43"

