

FreshVac[®]**Modified Atmosphere
Packaging Machines****A-300 PLC****FROM THE PIONEERS IN
MODIFIED ATMOSPHERE
PACKAGING**

Compact , portable and easy to use, the A-300 PLC serves a wide range of applications. Available as a tabletop unit or supported by an optional adjustable stand, the A-300 can be configured to fit virtually any packaging or laboratory environment. Although small in size, this reliable model has also the performance features necessary to meet today's demanding production needs.

PLC controls with pre-set pack settings give it the flexibility to handle a wide range of package sizes and configurations.

View our videos on-line by scanning the
QR code



Or go to www.cvpystems.com

*Cutting edge technology from the leader in modified atmosphere packaging.
Made with pride in the USA since*

**1972**

A-300 PLC MODEL DESIGN FEATURES

SOLUTIONS IN Modified Atmosphere Packaging

- All stainless steel construction
- CE Certification
- PLC Controls
- Red Meat: Case ready mother bags, sausage, deli meats, individual cuts
- Produce: Pre-cut fruits and vegetables, cherry micro perforated bags
- Fish: Case ready mother bags
- Cheese: Shredded cheese bags
- Nuts and snack foods: Bag in box
- Coffee packs



Design

- Stainless steel construction.
- CE Approved.
- PLC Controlled.
- Clean- in - place system.
- External wipe down capability.

Consistent Results

- 32-inch or 42-inch manifold with positive gas seal control.

Flexibility

- Multiple cycle selection allows seal only, vacuum only, vacuum/gas flush and double cycle.
- Rapid changeover optional shelves for ease of product handling and placement.
- Impulse wire sealing system seals through most material thicknesses.
- Venturi or electric vacuum pumps available to match product requirements.
- Ease of setup and installation allows quick startup.

Construction	Stainless Steel/Hard Anodized Aluminum
Vertical Stand	47" H x 29.5 W x 36" D
Dimensions	32" Manifold (36" H x 34" W x 14" D) 42" Manifold (36" H x 44" W x 14" D)
Power Requirements	Venturi Pump, 110/220 Volt AC, Single Phase Electric Pump, 230/440 Volt AC, Three Phase
Air Consumption	15 CFM @ 100 PSI for Venturi, 8 CFM @ 100 PSI for Electric Pump, 1/2 " I.D Min. Supply Line



2518 Wisconsin Avenue
Downers Grove, IL 60515 USA
Phone: (630) 852-1190
Website: www.cvpsystems.com
Email: sales@cvpsystems.com