

## PORTABLE CHILLER SPECIFICATIONS

## ELECTRICAL DATA

## BTUH

MODEL	DIMENSIONS (WxLxH)	TANK VOLUME (gallons)	PROCESS PUMP (HP)	GPM @ 25 PSI	OPERATING WEIGHT (approx lbs)	CONN- ECTION SIZE	208-240 / 1 / 60			208-240 / 3 / 60			460 / 3 / 60			LEAVING FLUID TEMP		
							RLA	MCA	MOC	RLA	MCA	MOC	RLA	MCA	MOC	20°F	30°F	40°F
CH-3	32" x 48" x 40"	30	0.75	25	980	0.75" OD x 4	27	30	51	18	21	32	8	10	15	17,213	21,436	26,098
CH-5	34" x 61" x 54"	50	1.5	40	1450	0.75" OD x 5	48	56	90	33	38	58	14	17	26	32,717	40,850	49,965
CH-7	34" x 61" x 54"	50	1.5	40	1450	0.75" OD x 5				41	47	74	16	19	30	41,395	51,046	61,824

## STANDARD FIRE AND ICE SPECIFICATIONS

## ELECTRICAL DATA

## BTUH

MODEL	DIMENSIONS (WxLxH)	TANK VOLUME (gallons)	PROCESS PUMP (HP)	GPM @ 25 PSI	OPERATING WEIGHT (approx lbs)	CONN- ECTION SIZE	208-240 / 1 / 60			208-240 / 3 / 60			460 / 3 / 60			HEATING @ 30°F		
							RLA	MCA	MOC	RLA	MCA	MOC	RLA	MCA	MOC	HEATING	COOLING	
CH-3/6	32" x 48" x 40"	30	0.75	25	990	0.75" OD x 4	29	30	40	21	27	30	9	11	15	20,500	21,436	
CH-3/10.5	32" x 48" x 40"	30	0.75	25	990	0.75" OD x 4				28	30	35	15	18	20	35,800	21,436	
CH-3/12.5	32" x 48" x 40"	30	0.75	25	990	0.75" OD x 4				38	45	45	17	22	25	42,700	21,436	
CH-3/21	32" x 48" x 40"	30	1.5	40	990	0.75" OD x 4							29	36	40	71,600	21,436	
CH-3/25	32" x 48" x 40"	30	1.5	40	990	0.75" OD x 4							33	42	45	85,300	21,436	
CH-5/8.5	34" x 61" x 54"	50	1.5	40	1450	0.75" OD x 5	48	59	60	28	33	40	14	17	20	29,000	40,850	
CH-5/10.5	34" x 61" x 54"	50	1.5	40	1450	0.75" OD x 5				30	37	45	16	20	25	35,800	40,850	
CH-7/12.5	34" x 61" x 54"	50	1.5	40	1450	0.75" OD x 5				41	52	60	18	23	25	42,700	51,046	

## STANDARD HEATER SPECIFICATIONS

## ELECTRICAL DATA

## BTUH

MODEL	DIMENSIONS (WxLxH)	TANK VOLUME (gallons)	PROCESS PUMP (HP)	GPM @ 25 PSI	OPERATING WEIGHT (approx lbs)	CONN- ECTION SIZE	MAX OPERATING TEMP (°F)	208-240 / 1 / 60			208-240 / 3 / 60			460 / 3 / 60			HEATING
								RLA	MCA	MOC	RLA	MCA	MOC	RLA	MCA	MOC	
GD-6	32" x 48" x 40"	30	0.75	25	780	0.75" OD x 4	125	29	30	40	21	27	30	9	11	15	20,500
GD-10.5	32" x 48" x 40"	30	0.75	25	780	0.75" OD x 4	125				28	30	35	15	18	20	35,800
GD-12.5	32" x 48" x 40"	30	0.75	25	780	0.75" OD x 4	125				38	45	45	17	22	25	42,700
GD-21	32" x 48" x 40"	30	1.5	40	780	0.75" OD x 4	125							29	36	40	71,600
GD-25	32" x 48" x 40"	30	1.5	40	780	0.75" OD x 4	125							33	42	45	85,300
GD-200K <sup>2</sup>	48" x 84" x 62"	115	5	150	1500	1.5"	150				15	18	30	8	9	15	200,000
GD-400K <sup>2</sup>	48" x 84" x 62"	115	5	150	1500	1.5"	150				15	18	30	8	9	15	400,000

## LSX SERIES

Designed for ultra-low temp applications ranging from 7.5HP – 180HP | Contact us for more details

<sup>2</sup> Stationary gas heater, available in LP or NG All capacities at 90°F ambient

1.800.555.0973 GDCHILLERS.COM



# G&D CHILLERS